

Law Offices of
YOUNG & BASILE, P.C.
Patents, Trademarks and Copyrights

3001 W. Big Beaver Rd., Ste. 624
Troy, MI 48064
Telephone: 248-649-3333
Facsimile: 248-649-3338

2001 Commonwealth Blvd., Ste. 301
Ann Arbor, MI 48105
Telephone: 734-662-0270
Facsimile: 734-662-1014

FACSIMILE TRANSMISSION

DATE: May 12, 2003
TO: Examiner W. Markham
FAX NO.: 703-872-8311
FROM: Michelle L. Knight
OUR REF.: SPM-290-A
YOUR REF.: S.N. 09/529,192
FOR: METHOD AND DEVICE FOR SURFACE-TREATING SUBSTRATES
PGS. TO FOLLOW: - 22 -
MESSAGE: Please see attached Amendment under 37 C.F.R. § 1.116 with Exhibit 1.

THE INFORMATION CONTAINED IN THIS FACSIMILE IS ATTORNEY PRIVILEGED AND/OR CONFIDENTIAL AND IS INTENDED ONLY FOR THE NAMED RECIPIENT. If you have received this communication in error, please notify us immediately. You are hereby notified that any dissemination, distribution or copying of this information is strictly prohibited. Thank you.

This message was transmitted by
Susan Dunlap in the Troy office. If
transmission difficulties occur,
please contact sender at (248) 649-
3333. Please respond to:
FACSIMILE NO. 248-649-3338

() Please call to confirm receipt
(X) Original will not follow
() Original will follow by:
____ Air Mail
____ Express Mail
____ Federal Express
____ Other _____

-2-

S.N. 09/529,192

Amendments to the Specification:

Please replace the last full paragraph on page 4, starting at line 25, with the following paragraph:

Substrate 1 can be grounded or connected to the ungrounded output of a voltage source such as that shown in Fig. 1. The voltage between substrate and a plasma formed by the electric discharge is preferably between one volt (V) and 3000 V, more preferably, between 100 V and 1000 V. Pulsed DC voltages with a pulse frequency between ten kHz and 100 kHz can also be considered as DC voltages. When low-frequency AC voltages are used, the frequency is preferably between 50 Hz and 60 Hz, and with intermediate-frequency AC voltages preferably between ten kHz and 100 kHz. High-frequency AC voltages preferably have frequencies between one MHz and 50 MHz. Instead of, or in addition to, supplying power with a voltage source, it can also be supplied by microwaves. The microwave frequencies are preferably in the gigahertz (GHz) range.